Rec'd PET/PTO 07 OCT 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 23 October 2003 (23.10.2003)

PCT

(10) International Publication Number WO 03/086570 A1

- (51) International Patent Classification⁷: B01D 17/038, 21/26
- (21) International Application Number: PCT/GB03/01253
- (22) International Filing Date: 24 March 2003 (24.03.2003)
- (25) Filing Language:

1

English

(26) Publication Language:

English

(30) Priority Data: 02252502.6

8 April 2002 (08.04.2002) EP

- (71) Applicant (for all designated States except US): COOPER CAMERON CORPORATION [US/US]; Suite 1700, 1333 West Loop South, Houston, TX 77027-9109 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HOPPER, Hans, Paul [GB/GB]; Hillhouse, Whiterashes, Aberdeenshire AB21 OQL (GB).
- (74) Agent: GILL JENNINGS & EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

086570 A

(54) Title: SEPARATOR

(57) Abstract: A separator for separating multiphase flow, the separator comprising: an inlet for a multiphase fluid; a plurality of outlets, at least one for each selected separator phase; and a main annular tubular bore through which the multiphase flow is caused to flow and to separate into lighter and heavier fluids, the bore having an outlet for each of the lighter and heavier fluids.